BANNER RANGE

APPLICATION	ARTICLE	ART-NO	COA-TING	WEIGHT	TENSILE STRENGTH	WIDTH UP TO	PRINT	FLAME RETARDANCY	TRANS-LUCENCY	OPEN %	AIR PERM.
backlit	backlit B1/M2	H6006-0301	PVC	500 g/m²	2900/2500 N/5 cm	500 cm	S, UV, L	B1, M2	30%		
	heylight B1	H5500-0303	PVC	680 g/m²	3400/3300 N/5cm	500 cm	S, UV, L	B1, NFPA 701 Test 1&2	30%		
frontlit	frontlit	H5022-0295	PVC	500 g/m²	2800/2100 N/5 cm	500 cm	S, UV, L	–			
	frontlit B1/M2	H6022-0295	PVC	500 g/m²	2700/2200 N/5 cm	500 cm	S, UV, L	B1, M2, Cal Adm Code			
	frontlit plus B1	H7022-0295-R	PVC-free	275 g/m²	2600/2250 N/5 cm	505 cm	S, UV, L	B1, EN 13501-1 (B-s1-d0), NFPA 701 Test 1			
	frontlit B1/M1	H6025-0295	PVC	500 g/m²	2600/2100 N/5 cm	500 cm	S, UV, L	B1, M1, NFPA 701 Test 1			
	frontlit premium B1/M1	H6471-0295	PVC	475 g/m²	2900/2400 N/5 cm	500 cm	S, UV, L	B1, M1, EN 13501-1 (B-s2-d0), NFPA 701 Test 2, FTPC Part 7			
mesh	mesh matt	H5024-0297	PVC	340 g/m²	2100/1500 N/5 cm	500 cm	S, UV, L	–		15%	1400 l/m³/s
	mesh plus B1	H7071-0295-R	PVC-free	185 g/m²	2300/1400 N/5 cm	505 cm	S, UV, L	B1, EN 13501-1 (B-s1-d0), NFPA 701 Test 1		15%	1400 l/m³/s
	mesh matt B1/M1	H5071-0297	PVC	340 g/m²	2100/1500 N/5 cm	500 cm	S, UV, L	B1, M1, EN 13501-1 (B-s2-d0)		15%	1400 l/m³/s
	mesh matt B1	H6071-0295	PVC	340 g/m²	2100/1500 N/5 cm	500 cm	S, UV, L	B1, EN 13501-1 (B-s1-d0), NFPA 701 Test 1		15%	1400 l/m³/s
blockout	blockout greyback plus B1	H7010-5126	PVC	325 g/m²	2500/2200 N/5 cm	505 cm	S, UV, L	B1, EN 13501-1 (B-s1-d0)			
	blockout B1/M2	H3512-0026	PVC	760 g/m²	2900/2500 N/5 cm	500 cm	S, UV, L	B1, M2, EN 13501-1 (B-s2-d0), NFPA 701 Test 2			
	blockout smooth basic W B1	H3535-0026	PVC	610 g/m²	2100/1900 N/5 cm	500 cm	S, UV, L	B1			
truck	truck 680 print glossy	8205 5945	PVC	680 g/m²	3000/3000 N/5 cm	300 cm	S, UV, L	–			
	sidecurtain 900 print	8556 5943	PVC	900 g/m²	4000/4000 N/5 cm	320 cm	S, UV, L	–			
	sidecurtain 900 print glossy	8556 5945	PVC	900 g/m²	4000/4000 N/5 cm	320 cm	S, UV, L	–			

plus = stands for added value – featuring defined material innovations such as GRS 4.0-certified recycled yarns or alternative technologies. Each product lists its specific features for full transparency

The technical data are approximate values based on average values determined. For manufacturing reasons, deviations of up to -5% are possible. These technical specifications respond to the current state of knowledge and are intended to provide information about our products without legal obligation. These data apply to new goods. Suggested applications do not release the buyer from the obligation to check whether the material is suitable for the intended use. The statements contained in this document apply to business customers in the B2B sector.
Our „plus“ rated products are manufactured with recycled yarns in the base fabric, certified to GRS 4.0 (100% rPET). Slight color variations may occur as a natural result of using recycled materials and do not represent a quality defect.

MehlerHeytex · Heytex Bramsche GmbH · Heywinkelstr. 1 · 49565 Bramsche · Germany · mehlerheytex@freudenberg-pm.com · www.mehlerheytex.com

TEXTILE RANGE

APPLICATION	ARTICLE	ART-NO	COATING	WEIGHT	TENSILE STRENGTH	WIDTH UP TO	PRINT	FLAME RETARDANCY	TRANS-LUCENCY	THICK-NESS
frontlit	decoflex B1/M1	H7304-5501	treatm	215 g/m²	300/1200 N/5 cm	505 cm	UV, L, DyeS	B1, M1, EN 13501-1(B-s1-d0), NFPA 701 Test 1		
	display B1	H7313-0295	PUR	235 g/m²	300/1200 N/5cm	500 cm	S, UV, L	B1, EN 13501-1 B-s1-d0), NPFA 701 Test 1		0,41 mm
blockout	nightfever soft plus B1	H7388-5975-R	waterbased	245 g/m²	350/600 N/5 cm	515 cm	UV, L, DyeS	B1, EN 13501-1 (B-s1-d0)	<1%	0,40 mm
	nightfever stretch B1	H7389-5975	waterbased	255 g/m²	350/600 g/m²	510 cm	UV, L, DyeS	B1, EN 13501-1 B-s1-d0), NPFA 701 Test 1	<1%	0,40 mm
	whitenight soft plus B1	H7398-5126-R	water based	280 g/m²	350/600 N/5 cm	505 cm	UV, L	B1, EN 13501-1 B-s1-d0), NPFA 701 Test 1	<1%	0,40 mm
	doubleface plus B1	H7490-5126-R	water based	440 g/m²	800/1100 N/5 cm	505 cm	UV, L	B1, EN 13501-1 B-s1-d0), NPFA 701 Test 1	<1%	0,75 mm

plus = stands for added value – featuring defined material innovations such as GRS 4.0-certified recycled yarns or alternative technologies. Each product lists its specific features for full transparency

INTERIOR RANGE

APPLICATION	ARTICLE	ART-NO	COATING	WEIGHT	TENSILE STRENGTH	WIDTH UP TO	PRINT	FLAME RETARDANCY
wallcover	airtex® decor greyback B1	H6805-B971	PVC	400 g/m²	1200/1000 N/ 5cm	500 cm	S, UV	B1, EN 13501-1 (B-s2-d0)
	airtex® decor whiteback B1	H6805-0292	PVC	400 g/m²	1200/1000 N/ 5cm	500 cm	S, UV	B1, EN 13501-1 (B-s2-d0)

KEY BENEFITS

- Developed with German engineering standards - for consistent quality wordwide
- PVC-free variants with GRS-certified recycled yarns – with verified CO^2 services available on request
- Reliable performace available from stock - at a price that makes sense

KEY BENEFITS

- Printing process legend
  S= Solvent, L= Latex, DyeS = DyeSub, UV = UV inks
- Service excellence - familiar, dependable and always close to you
- From development to delivery - our materials undergo continuous quality checks to ensure lasting reliability

For direct support or more information on our Sign materials please contact

- order.heysign@freudenberg-pm.com

Status: 04.11.2026