TECHNICAL DATA SHEET

Technical datasheet No.: 1840.12

8115 0641

mat 600 leather top PF

PROPERTIES			
Type of coating		PVC one side	
Finish		one side with Acryl lacquer, leather embossing (outside)	
Total weight		600 g/m²	EN ISO 2286-2
Tensile strength	warp/weft	2500 / 2500 N/50 mm	EN ISO 1421/V1
Tear strength	warp/weft	250 / 250 N	DIN EN 17679
Adhesion		15 N/cm	PA 09.03 (intern)
Cold resistance.		-30 °C	EN 1876-1
High Temperature		+70 °C	PA 07.04 (intern)
Light fastness		>6 Note, Value	EN ISO 105 B02
Material		PES	DIN EN ISO 2076
Yarn count		1100 dtex	DIN EN ISO 2060
Weave		L 1/1	ISO 3572
Remarks		Tested according to DIN EN 71-3, please ask for the test report to check suitability for a specific application	
Special Features		phthalate-free according to EC (EU) Nr. 1907/2006 (REACH) annex XVII, entry 52 legal limits for toys and childcare articles	

The technical data are approximate values based on average values determined. For manufacturing reasons, deviations of up to -5% are possible. These technical specifications respond to the current state of knowledge and are intended to provide information about our products without legal obligation. These data apply to new goods. Suggested applications do not release the buyer from the obligation to check whether the material is suitable for the intended use.

Bei den technischen Daten handelt es sich um ca. Werte, die auf Basis von ermittelten Durchschnittswerten erstellt wurden. Aus fertigungstechnischen Gründen sind Abweichungen bis zu -5% möglich. Diese technischen Angaben entsprechen dem heutigen Stand der Kenntnisse und sollen über unsere Produkte ohne Rechtsverbindlichkeit informieren. Diese Daten gelten für neue Ware. Einsatzvorschläge entbinden den Käufer nicht, selbst zu prüfen, ob das Material für den von ihm gewünschten Einsatz geeignet ist.

MehlerHeytex · Mehler Texnologies GmbH · Rheinstraße 11 · 41836 Hückelhoven · Germany · mehlerheytex@freudenberg-pm.com ·

Version 03.2026

VL/LB:

MehlerHeytex

a brand of FREUDENBERG