Technical datasheet No.: 1265.17

8602 1300

divider 1200

PROPERTIES		
Type of coating	PVC	
Finish	textured surface	
Burning behaviour	DIN 4102: B1, ÖNorm: B1, GOST: G1, EN 13501-1: B-s1-d0	
for Burning behaviour	always check validity of fire certificate, also check country-specific validity	
Total weight	1200 g/m²	EN ISO 2286-2
Tensile strength warp/weft	1500 / 1500 N/50 mm	EN ISO 1421/V1
Tear strength (S) warp/weft	200 / 200 N	DIN 53356
Cold resistance	-10 °C	EN 1876-1
High Temperature	+70 °C	PA 07.04 (intern)
Material	PES	DIN EN ISO 2076
Yarn count	1100 dtex	DIN EN ISO 2060
Weave	M Tex	
Remarks	complies with DIN 18032-4, Compliant with the AgBB Scheme 2024	

The technical data are approximate values based on average values determined. For manufacturing reasons, deviations of up to -5% are possible. These technical specifications respond to the current state of knowledge and are intended to provide information about our products without legal obligation. These data apply to new goods. Suggested applications do not release the buyer from the obligation to check whether the material is suitable for the intended use.

Bei den technischen Daten handelt es sich um ca. Werte, die auf Basis von ermittelten Durchschnittswerten erstellt wurden. Aus fertigungstechnischen Gründen sind Abweichungen bis zu -5% möglich. Diese technischen Angaben entsprechen dem heutigen Stand der Kenntnisse und sollen über unsere Produkte ohne Rechtsverbindlichkeit informieren. Diese Daten gelten für neue Ware. Einsatzvorschläge entbinden den Käufer nicht, selbst zu prüfen, ob das Material für den von ihm gewünschten Einsatz geeignet ist.

MehlerHeytex · Mehler Texnologies GmbH · Rheinstraße 11 · 41836 Hückelhoven · Germany · mehlerheytex@freudenberg-pm.com ·

Version 03.2026

VL/LB: