BARRIER 1050 BL LQ | H4553

Advanced PVC/TPU blend containment boom material withsmooth lacquered finish. High flexibility for fast deployment and easy field handling.

barrier 1050 BL LQ features a PVC/TPU blend with a lacquered finish that improves handling during fabrication and deployment in the field. The material can be bent cleanly without creasing, making it ideal for booms that need to be packed away, stored and redeployed frequently. PVC/TPU blend formulation provides extra abrasion resistance combined with chemical resistance and long-term durability. The lacquer coating improves sliding and reduces wear. It is a practical choice where ease of use and an extended service life are equally important.



German Engineered

Durable Coating Performance

high adhesion and hydrolysis resistance extend lifespan in wet environments

Robust Marine Durability

withstands seawater, oils, and chemicals for reliable performance

Stable Performance

withstand waves, wind, and currents for stable and reliable performance in challenging marine conditions

Superior Stability

PVC/TPU Blend & acrylic lacquer – providing extra protection

Weather Resistance

state-of-the-art UV stabilizers ensures a reliable weather resistance

Status: 03.2026

Other colors on request

The technical data are approximate values based on average values determined. For manufacturing reasons, deviations of up to -5% are possible. These technical specifications respond to the current state of knowledge and are intended to provide information about our products without legal obligation. These data apply to new goods. Suggested applications do not release the buyer from the obligation to check whether the material is suitable for the intended use.

Image: shutterstock/ElisaPutti