# OFFSHORE 1250 BL LQ | H4583

**Advanced PVC/TPU blend formulation for highest demands.**
**Strong adhesion and durability for harsh offshore conditions.**

offshore 1250 BL LQ adds a lacquered finish to the tried-and-tested PVC/TPU blend, providing technicians with a smoother and cleaner fabrication process. The lacquer improves handling by reduction of surface friction, supports consistant welding and gives extra UV protection. In offshore conditions, the fabric retains its structural integrity when subjected to currents, towing forces and chemical exposure.

It withstands wear during long deployments, providing teams who depend on equipment that can withstand continuous use with practical reliability.



German Engineered

**Durable Coating Performance**
high adhesion and hydrolysis resistance extend lifespan in wet environments

**Robust Marine Durability**
withstands seawater, oils, and chemicals for reliable performance

**Stress Resistant**
maintains stability and strength even under continuous mechanical stress in offshore applications

**Superior Stability**
PVC/TPU Blend & acrylic lacquer – providing extra protection

**Weather Resistance**
state-of-the-art UV stabilizers ensures a reliable weather resistance

Status: 03.2026

**Other colors on request**

The technical data are approximate values based on average values determined. For manufacturing reasons, deviations of up to -5% are possible. These technical specifications respond to the current state of knowledge and are intended to provide information about our products without legal obligation. These data apply to new goods. Suggested applications do not release the buyer from the obligation to check whether the material is suitable for the intended use.

Image: Norlense, NO

MehlerHeytex