DOCKSHELTER 2500 SINGLE LQ | 7806 5342

Durable and flexible 2500 Single LQ Dockshelter is designed for reliable sealing and a long service life in loading bays. Its single-layer construction provides better flexibility than multi-layer systems.

The 2 mm material thickness ensures stability for safe and reliable operation, while offering flexibility in demanding environments. The durable lacquer system protects against wear and tear, extending the service life and maintaining the appearance. Its high abrasion resistance allows for continuous contact with vehicles, and excellent dimensional stability ensures shape retention. Available in widths up to 210 cm, it supports the fabrication of large dock shelter components.



German Engineered

Status: 22.07.2026

Abrasion Resistance

designed to withstand repeated contact and mechanical wear in daily loading operations

Dimensional Stability

maintains shape and size under temperature changes and continuous operation

Reliable strength

2 mm material thickness supports robust and safe operation in demanding loading environments

Protected Surface

high-quality lacquer system provides durable surface protection for long-term use

DOCKSHELTER 2500 SINGLE LQ | 7806 5342



905
black

Available width: 210 cm. Other widths on request.

Other colors on request. Print colors may differ from the original depending on the paper and printing process.

The technical data are approximate values based on average values determined. For manufacturing reasons, deviations of up to -5% are possible. These technical specifications respond to the current state of knowledge and are intended to provide information about our products without legal obligation. These data apply to new goods. Suggested applications do not release the buyer from the obligation to check whether the material is suitable for the intended use.