

STORAGE TENT 650 FR GL | H1150-A

Strong. Reliable. Cost-Optimized. Essential Performance, Smart Protection.

There are projects where budgets are tight, schedules are rushed, and reliability becomes the only true luxury. In these moments, storage tent 650 FR steps in as the dependable companion that simply does its job – quietly, consistently, without fuss. It welds cleanly, stands firm in sun and rain, and keeps its smooth surface unbothered by dirt or wear.

Flame-retardant by design and steady across changing temperatures, it's the material you choose when you need honesty, clarity, and trustworthy performance.



Adhesion

150 N/5 cm - high adhesion, which ensures strong welding seams



Certified

European FR certificates according to different norms (for further details, please see data sheet)



High Gloss

smooth and glossy surface for convincing dirt resistance



Tensile Strength

high tensile in combination with light weight ready made tents



Weather Resistance

state-of-the-art UV stabilizers ensures a reliable weather resistance



Weldability

excellent weldability and less smoke during welding

Standard width: 250 cm.

The technical data are approximate values based on average values determined. For manufacturing reasons, deviations of up to -5% are possible. These technical specifications respond to the current state of knowledge and are intended to provide information about our products without legal obligation. These data apply to new goods. Suggested applications do not release the buyer from the obligation to check whether the material is suitable for the intended use.

Image: GettyImages/NejcGostincar