

STORAGE TENT 750 FR BLO GL | H1175-A

Light Blocked. Safety Secured. Zero Light. Maximum Protection.

Some environments demand more than shade – they demand control. storage tent 750 FR BLO creates that control effortlessly. Behind its smooth, confident surface lies a blackout core that turns harsh sunlight into calm darkness, giving people and equipment a space that feels protected, focused, intentional. Its lightweight build moves easily from one location to the next, yet its flame retardant structure and stable performance in shifting weather never waver.

It's the material you choose when you need mobility, safety, and atmosphere - delivered in one quiet, powerful gesture.



Adhesion

150 N/5 cm - high adhesion, which ensures strong welding seams



Blockout

100% in combination with light weight material for light weight tents



Certified

European FR certificates according to different norms (for further details, please see data sheet)



Tensile Strength

high tensile in combination with light weight ready made tents



Weather Resistance

state-of-the-art UV stabilizers ensures a reliable weather resistance



Weldability

excellent weldability and less smoke during welding

Standard width: 250 cm.

The technical data are approximate values based on average values determined. For manufacturing reasons, deviations of up to -5% are possible. These technical specifications respond to the current state of knowledge and are intended to provide information about our products without legal obligation. These data apply to new goods. Suggested applications do not release the buyer from the obligation to check whether the material is suitable for the intended use.

Image: GettyImages/NejcGostincar